

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/114535 A1

(51) International Patent Classification⁷: **H04B 1/707**

(74) Agents: CROSS, James, P., A. et al.: R G C Jenkins & Co., 26 Caxton Street, London SW1H 0RJ (GB).

(21) International Application Number:
PCT/GB2003/003288

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 29 July 2003 (29.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0313904.5 16 June 2003 (16.06.2003) GB

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): IN-MARSAT LTD. [GB/GB]; 99 City Road, London EC1Y 1AX (GB).

(72) Inventor; and


Published:

— with international search report

(75) Inventor/Applicant (*for US only*): GRANT, Alexander [AU/AU]; c/o Institute For Telecommunications Research, University Of South Australia, SPRI Building, Mawson Lakes Boulevard, Mawson Lakes SA 5095 (AU).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COMMUNICATION METHOD AND APPARATUS FOR MULTI-USER DETECTION



(57) Abstract: In a multi-user detection receiver, a multi-user detector DET receives a signal from a multiple access channel MA and the current soft estimates of each user's contribution to the received signal, and outputs updated soft estimates for each user by subtracting the current soft estimates of all the interfering users. The updated soft estimate or soft demodulated by soft demodulators DEM_1, \dots, DEM_K , the coded by soft decoders $DEC_1 \dots DEC_K$ which refine the probabilities of the coded bits derived from the soft demodulators DEM_1, \dots, DEM_K by taking into account the knowledge of the code, and output to soft modulators $M_1 \dots M_K$. For each iteration of the MUD receiver algorithm, an acquisition function ACQ acquires the timing of the estimates of each user's contribution to the channel for use by the detector DET in the next iteration, giving improved acquisition performance over conventional single-user techniques.